



Guaranteed Minimum Analysis

MACRONUTRIENTS

Total Nitrogen (N)	13.00%
2.21% Urea Nitrogen	
10.79% Methylene Urea	
Available Phosphoric acid (P2O5)	2.00%
Soluble Potash (K2O)	26.00%
26.00% Sulphate of Potash	
MICRONUTRIENTS	
Sulfur (S)	8.00%

Analyse Minimale Garantie

MACRONUTRIENTS

Azote total (N)	13,00%
2,21% Azote Urée	
10,79% Méthylène Urée	
Disponible Acide phosphorique (P2O5)	2,00%
Potasse soluble (K2O)	26,00%
26,00% sulfate de potasse (SOP)	
MICRONUTRIENTS	
Soufre (S)	5,00%

Product derived from: Methylene Urea, Urea, Mono ammonium phosphate, Sulphate of Potash, Calcium Carbonate
Active ingredients derived from registered and exempt materials.

Directions for Use : Apply 6.7 bags per acre (4,047 m2) to obtain 1 lb. (0.45 kg) of nitrogen per 1,000 ft2. (93 m2)
Apply to turf as needed. To be used as part of a complete fertilization program. This product should be used on the basis of a soil and/ or tissue analysis.

Produit dérivé de : Méthylène urée, urée, phosphate mono ammoniacal, sulfate de potasse, carbonate de calcium. Ingrédients actifs dérivés de matières enregistrées et exemptées.

Mode D'emploi : Appliquer 6,7 sacs par acre (4 047 m2) pour obtenir 1 lb (0,45 kg) d'azote par 1 000 pi2 (93 m2). (93 m2). Appliquer sur le gazon au besoin. À utiliser dans le cadre d'un programme complet de fertilisation. Ce produit doit être utilisé sur la base d'une analyse du sol et/ou des tissus.



Guaranteed by, manufactured for/ garantie par, fabriqué pour:
Target Specialty Products PO Box 278 Milton, ON Canada L9T 4N9

13-2-26

Greens High K, 83% Methylene Urea
Verts Haute K, 83% Mehtylene Urea
90 SGN

SUGGESTED SPREADER SETTINGS / RÉGLAGES SUGGÉRÉS POUR L'ÉPAN-
DEUR:

These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product. Ces suggestions de réglages de l'épandeur ne sont pas destinées à remplacer l'étalonnage. Veuillez calibrer votre épandeur avant d'appliquer le produit.

SPREADER épandeur	GROUND SPEED vitesse au sol	WIDTH OF COVERAGE largeur de la couverture	TOTAL PRODUCT/ produit total	
			LOW RATE faible taux 3.0 lbs/1,000 sq ft	MEDIUM RATE taux moyen 4.0 lbs/1,000 sq ft
AccuPro 2000	3 mph/ 4.8 km/h	10 ft/ 3 m	L	M
Earthway 2400	3 mph/ 4.8 km/h	8 ft/ 2.4 m	15	16
Lely Models WR, WFG, HR 1240 (PTO @ 450 rpm)	4.5 mph/ 7.2 km/h	30 ft/ 9.1 m	5 ll	6 ll
Lesco (letters)	3 mph/ 4.8 km/h	7 ft/ 2.1 m	H	J
Lesco (numbers)	3 mph/ 4.8 km/h	7 ft/ 2.1 m	16	21
Prizelawn CBR III	3 mph/ 4.8 km/h	8 ft/ 2.4 m	J	N
Prizelawn CBR II	3 mph/ 4.8 km/h	8 ft/ 2.4 m	4	5 1/2
Scotts R8	3 mph/ 4.8 km/h	10 ft/ 3 m	K	M
Spyker	3 mph/ 4.8 km/h	8 ft/ 2.4 m	3	4 3/4

Net Weight/ poids net
22.68 kg (50 lb)

