



16-32-6

Starter (démarreur) 50% PCU
250 SGN

Guaranteed Minimum Analysis

MACRONUTRIENTS

Total Nitrogen (N)16.00%
50% (8 out of 16) polymer-coated Urea
Available Phosphoric acid (P₂O₅)32.00%
Soluble Potash (K₂O)6.00%

MICRONUTRIENTS

Sulfur (S)2.70%

Product derived from: Monoammonium Phosphate, Polymer Coated Sulphur Coated Urea, Muriate of Potash, Urea, Calcium Carbonate. Active ingredients derived from registered and exempt materials.

Directions for Use

Apply 2.5 bags per acre (4,047 m²) to obtain 1 lb. (0.45 kg) of phosphorous per 1,000 ft² (93 m²). Additional seasonal applications should be completed based on a soil and/ or tissue analysis. To be used as part of a complete fertilization program.

Analyse Minimale Garantie

MACRONUTRIENTS

Azote total (N)16,00%
50 % (8 sur 16) d'urée enrobée de polymère
acide phosphorique (P₂O₅)32,00%
Potasse soluble (K₂O)6,00%

MICRONUTRIENTS

Soufre (S)2,70%

Produit dérivé de : Phosphate monoammonique, urée soufrée enrobée de polymère, muriate de potasse, urée, carbonate de calcium. Ingrédients actifs dérivés de matières enregistrées et exemptées.

Mode D'emploi

Applique 2.5 sacs par acre (4,047 m²) pour obtenir 1 lb. (0.45 kg) de phosphore par 1000 pi² (93 m²). es applications saisonnières supplémentaires doivent être effectuées sur la base d'une analyse du sol et/ou des tissus. A utiliser dans le cadre d'un programme complet de fertilisation.

SUGGESTED SPREADER SETTINGS / RÉGLAGES SUGGÉRÉS POUR L'ÉPANDEUR:

These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product. Ces suggestions de réglages de l'épandeur ne sont pas destinées à remplacer l'étalonnage. Veuillez calibrer votre épandeur avant d'appliquer le produit.

SPREADER épandeur	GROUND SPEED vitesse au sol	WIDTH OF COVERAGE largeur de la couverture	SPREADER SETTINGS (Total Product)	
			LOW RATE faible taux 1.9 lbs/1,000 sq ft	MEDIUM RATE taux moyen 3.0 lbs/1,000 sq ft
AccuPro 2000	3 mph/ 4.8 km/h	10 ft/ 3 m	K	L
Earthway 2400	3 mph/ 4.8 km/h	8 ft/ 2.4 m	14	15
Lely Models WR, WFG, HR 1240 (PTO @ 450 rpm)	4.5 mph/ 7.2 km/h	30 ft/ 9.1 m	4 ll	5 ll
Lesco (letters)	3 mph/ 4.8 km/h	7 ft/ 2.1 m	G	I
Lesco (numbers)	3 mph/ 4.8 km/h	7 ft/ 2.1 m	15	17
Prizelawn CBR III	3 mph/ 4.8 km/h	8 ft/ 2.4 m	I	L
Prizelawn CBR II	3 mph/ 4.8 km/h	8 ft/ 2.4 m	4	4 1/2
Scotts R8	3 mph/ 4.8 km/h	10 ft/ 3 m	K	L

Net Weight/ poids net
25 kg (55 lb)



Guaranteed by, manufactured for/ garantie par, fabriqué pour:
Target Specialty Products PO Box 278 Milton, ON Canada L9T 4N9



CI601680